

## RANGE SUMMARY

The SuperSafe SBS range utilises unique and proven technology to provide a superior range of valve regulated batteries with an extended service life in compact and energy dense configurations. SuperSafe SBS is manufactured to the highest international standards and is ideal for reliable use in all wireless and fixed-line communication applications. SuperSafe SBS is also widely used in cable TV, emergency lighting, power generation and offshore applications.

The SuperSafe SBS is available in several configurations including the front terminal series which are becoming increasingly popular in leading edge telecom applications. Smaller than the competition, the front terminal series offers design flexibility where space is limited and will easily fit in cabinets and 19" or 23" rack configurations.

SuperSafe SBS batteries are designed to cope with raised temperatures and harsh environments. The advanced plate technology and manufacturing methods, used by EnerSys, make SuperSafe SBS the choice for long and trouble-free service. The maximum operating temperature of the SuperSafe SBS J series can be extended to 80°C (176°F) via an optional metal jacket.

### Features & Benefits

- Capacity range: 7Ah - 360Ah
- Proven long service
- High energy density
- Up to two year shelf life
- Very low ventilation requirement
- 2V, 6V, and 12V configurations
- Wide operating temperature range:  
-40°C (-40°F) to 50°C (122°F)



## Construction

- Positive plate - pure lead grid using a unique manufacturing process
- Negative plate - pure lead grid
- Separator - superior quality microporous glass mat separator with high absorption and stability
- Case material - impact resistant material, flame retardant to UL94 V-0 (J types are Noryl, all others are ABS)
- Electrolyte - medical grade dilute sulphuric acid absorbed into separator material
- Terminal design - leak resistant dual seal terminal design

## Operation

- Recommended float charge voltage: 2.29Vpc @ 20°C (68°F) or 2.27Vpc @ 25°C (77°F)
- The SuperSafe SBS range of batteries can be mounted in any orientation except inverted
- SuperSafe SBS was designed for use in cabinets, or on stands, close to the point of use. A separate battery room is not required
- SuperSafe SBS is ideal for installation as an integral part of a standby system due to its long life
- SuperSafe SBS is also available for underwater applications

## Standards


- Fully compliant with BS 6290 Part 4 (1997)
- Conforms to IEC 60896-2 and Telcordia SR-4228
- Recognised by UL (UL Standard 1989)
- Approved as non-hazardous cargo for ground, sea and air transportation in accordance with US DOT Regulation 49 and ICAO & IATA Packing Instruction 806
- Manufactured in EnerSys production facilities certified to ISO 9001:2000

## General Specifications


Type	Number of Cells	Nominal Voltage (V)	Nominal Capacity (Ah)		Nominal Dimensions						Typical Weight		Short Circuit Current (A) <sup>(3)</sup>	Internal Resistance (mΩ) <sup>(3)</sup>	Terminals
			10 hr rate to 1.80Vpc @ 20°C	8 hr rate to 1.75Vpc @ 77°F	Length		Width		Height		kg	lbs			
SBS 8	6	12	7	7	138	5.4	86	3.4	101	4.0	2.7	5.9	455	27.1	M4 F
SBS 15	6	12	14	14	200	7.9	77	3.0	140	5.5	5.7	12.5	891	13.5	M6 M
SBS 30	6	12	26	26	250	9.8	97	3.8	156	6.1	9.5	20.9	1556	7.9	M6 M
SBS HB30 <sup>(1)</sup>	6	12	26	26	250	9.8	97	3.8	156	6.1	9.6	21.1	1556	7.9	harness
SBS 40	6	12	38	38	250	9.8	97	3.8	206	8.1	12.7	28.0	2184	5.6	M6 M
SBS 60	6	12	51	51	220	8.7	121	4.8	261	10.3	18.5	40.7	2618	4.4	M6 M
SBS 110	3	6	115	116	200	7.9	208	8.2	239	9.4	21.2	46.6	3804	1.7	M8 M
SBS 130	3	6	132	133	200	7.9	208	8.2	239	9.4	22.7	49.9	4111	1.4	M8 M
SBS 300	1	2	310	307	200	7.9	208	8.2	239	9.4	21.7	47.7	8700	0.23	M8 M
SBS 390	1	2	360	361	200	7.9	208	8.2	239	9.4	23.2	51.0	11101	0.18	M8 M
SBS J13	6	12	12	12	175	6.9	83	3.3	129	5.1	5.7	12.6	957	13.0	M6 F
SBS J16	6	12	15	15	181	7.1	76	3.0	167	6.6	6.7	14.8	1111	11.0	M6 F
SBS J30	6	12	26	26	166	6.5	175	6.9	125	4.9	11.8	26.0	1766	7.0	M6 F
SBS J40	6	12	39	39	196	7.7	165	6.5	170	6.7	17.4	38.2	2400	5.2	M6 F
SBS J70	6	12	64	64	329	12.9	166	6.5	174	6.9	27.6	60.9	3500	3.5	M6 F
SBS B8 <sup>(2)</sup>	6	12	31	31	280	11.0	97	3.8	159	6.3	10.3	22.7	1584	7.7	M8 F
SBS B10 <sup>(2)</sup>	6	12	38	38	280	11.0	97	3.8	184	7.2	12.8	28.2	1968	6.2	M8 F
SBS B14 <sup>(2)</sup>	6	12	62	62	280	11.0	97	3.8	264	10.4	19.1	42.0	3210	3.8	M8 F
SBS C11 <sup>(2)</sup>	6	12	92	91	395	15.6	105	4.1	264	10.4	28.0	61.6	3696	3.3	M8 F

### Notes


- <sup>(1)</sup> SBS HB30 is fitted with a 533mm/21 inch harness that terminates in a 2-pin polarised plug-in connector which is compatible with embedded power SLC systems.  
<sup>(2)</sup> SBS B & C types are available with terminals on the top face or on the front face. For front face terminals add 'FT Adapter' to the model number.  
<sup>(3)</sup> Figures obtained via BS6290 method.



SBS 8 to 60 & J types



SBS B & C types



SBS 110 to 390



www.enersysinc.com

**Global Headquarters**  
 P.O. Box 14145 Reading  
 PA 19612-4145  
 USA  
 Tel: +1-610-208-1991  
 +1-800-538-3627  
 Fax: +1-610-372-8613

**EnerSys EMEA**  
 Houtweg 26  
 1140 Brussels  
 Belgium  
 Tel: +32 (0)2 247 94 47  
 Fax: +32 (0)2 247 94 49

**EnerSys Asia**  
 49, Yanshan Road  
 Shekou, Shenzhen  
 Guangdong 518066  
 China  
 Tel: +86-755-2689 3639  
 Fax: +86-755-2689 8013

Contact: